
**elbaC Cable**

ZAC sous le Beer - RD 836
F-27730 BUEIL (Eure - France)
Tél : +33 (0)2 32 62 00 92
Fax : +33 (0)2 76 01 31 80
www.elbac.fr / info@elbac.fr

**Construction****Inner conductor** ①-④

Material	Annealed Copper
Diameter	AWG24 / $\varnothing 0.50 \pm 0.008$ mm

Insulation ①-④

Material	PEHD
Diameter	$\varnothing 0.95$ mm

Assembly

4 unshielded pairs

①		Blue / White blue
②		Brown / White brown
③		Orange / White orange
④		Green / White green

Mylar spiral ⑤

Coverage	$\geq 125\%$
----------	--------------

Drain wire ⑥

Material	Tinned Copper
Diameter	$\varnothing 0.50 \pm 0.008$ mm

Screen ⑦

Material	Aluminium / PET (40 μ /12 μ)
Diameter	$\geq 125\%$

Sheath ⑧

Material	LSZH
Color	Grey RAL 7035
Diameter	$\varnothing 6.00 \pm 0.15$ mm

Weight

Linear mass	42 kg/km
-------------	----------

Marking of sheath

Printing	ISO 11801 - FTP CAT 5E 4 PR 24 with XXX : Quantity in meter still available per reel DDDDD : Date code
	AWG LSZH EIA/TIA 568A - elbaC 250436 - DDDDD - XXX m

Color / Process	Black / Ink jet
-----------------	-----------------

Step	1 m
------	-----

Meet Standards

Electrical :	EIA/TIA 568A - ISO/IEC 11801
Fire performance :	IEC 60332-1 NF C 32-070 Classe C2
Fire reaction :	EN 50575:2014/A1:2016
Smoke density :	IEC 61034
Halogen free :	IEC 60754
Environment :	European directive 2011/65/EU
Marking :	CE

Electrical characteristics

Impedance	$100 \pm 15 \Omega$
-----------	---------------------

Max. conductor DC resistance	94.8 Ω /km
------------------------------	-------------------

Propagation velocity	65%
----------------------	-----

Performances

Frequency MHz	Max attenuation dB/100m	NEXT dB	RL dB
0.77	1.82	67.0	22.60
1.00	2.00	65.3	23.10
4.00	4.10	56.3	23.00
8.00	5.80	51.8	24.50
10.00	6.50	50.3	25.00
16.00	8.20	47.3	25.00
20.00	9.30	45.8	25.00
25.00	10.23	44.3	24.20
31.25	11.71	42.9	23.30
62.50	17.25	38.4	20.70
100.00	22.00	35.3	19.24

Frequency MHz	ACR dB	ELFEXT dB	PS ELFEXT dB
0.77	64.0	66.0	63.0
1.00	62.3	63.8	60.8
4.00	53.3	51.7	48.7
8.00	48.8	45.7	42.7
10.00	47.3	43.8	40.8
16.00	44.3	39.7	36.7
20.00	42.8	37.7	34.7
25.00	41.3	35.8	32.8
31.25	39.9	33.9	30.9
62.50	35.4	27.8	24.8
100.00	32.3	23.8	20.8

Thermal characteristics

CPR fire reaction class	E _{ca}
-------------------------	-----------------

Rated temperature	60°C
-------------------	------

Packaging

- R3 : 305m / Easy Reel Box

Notes